

100Ft Illumination Day/Night Bullet Camera



WDB-1000VDN (STD Res. / Sony Super HAD CCD)
WDB-1005VDN (High Res. / Sony Super HAD CCD)
WDB-1005VEX (High Res. / Sony Ex-View HAD CCD)

MAIN FEATURES

- Infra-Red LED Illuminators (100Ft)
- Vari-Focal Lens with Auto Iris
- Sunshield
- External Lens Adjustment
- Weatherproof Housing
- Cable Protected Mounting Bracket

SPECIFICATIONS

Model	WDB-1000VDN	WDB-1005VDN	WDB-1005VEX
Image Sensor Format	1/3" Sony Super HAD / STD Resolution	1/3" Sony Super HAD / High Resolution	1/3" Sony Ex-View HAD / High Resolution
Effective Pixels	NTSC: 510(H) x 492(V), PAL: 500(H) x 582(V)	NTSC: 768(H) x 494(V), PAL: 752(H) x 582(V)	NTSC: 768(H) x 494(V), PAL: 752(H) x 582(V)
H. Resolution	380 TV Lines	480 TV Lines	480 TV Lines
Scanning System	NTSC 525 Lines / PAL 625 Lines - 2:1 Interlaced		
Video Output Level	1.0Vp-p Composite, 75 ohms		
S/N Ratio	More than 50dB (AGC Off)		
BLC	ON/OFF SW		
Shutter Speed	NTSC: 1/60 ~ 1/100,000 sec / PAL: 1/50 ~ 1/100,000 sec		
Gamma Correction	r = 0.45		
White Balance	2100°K ~ 9200°K Auto		
Gain Control	4dB ~ 32dB Auto		
IR LED Visibility Range	Visible 5mm Diameter (850nm) ±10° X 23EA / ±20° X24EA, Real 30 Meter (Approx 100 Feet), 47pcs		
Min. Illumination	1.0 Lux (IR LED Off) / 0 Lux (IR LED On)		
CDS Sensor(Approx)	IR LED On/Off at 1~5 Lux		
Lens	Standard: Vari Focal 4-9mm Auto DC Iris Day & Night Lens (STD) Options: Vari Focal 4-9mm, 2.6-6mm, 9-20mm Auto DC Iris (Day & Night) Lens		
Operating Temperature	14°F ~ 122°F (-10°C ~ + 50°C)		
Humidity	10% - 95% RH		
Power Source	AC/DC Dual Power - AC(19.6V~28.8V) / DC (DC12V ~ DC24V)		
Operating Current	DC12V / 570mA or AC24 - 220mA, Regulated Power Input		
Dimensions	84mm x 84mm x 116mm / 3.3" x 3.3" x 4.6" (W x H x D)		
Weight(Approx)	900g / 2lbs (With Sunshield)		
Output Terminal	4 Feet Cable with BNC Female for Video, DC Jack-Male or Wire for Power		

WELDEX CAN CUSTOMIZE CAMERAS FOR YOUR SPECIFIC NEED!!